FALL PROTECTION FIELD REFERENCE GUIDE **HARNESS INSPECTION**



WHEN CONDUCTING AN INSPECTION, IT IS IMPORTANT TO UNDERSTAND THE ENVIRONMENT IN WHICH THE EQUIPMENT WAS USED (I.E. CHEMICAL, PARTICULATE, HEAT, ETC.)

ALWAYS REFER TO THE MANUFACTURER'S RECOMMENDED REMOVAL CRITERIA

HARDWARE

 \mathbf{V}

Inspect harness hardware including buckles, adjusters, D-ring, link, loop keepers, lanyard parking, etc. These items shall not be damaged, broken, or distorted and must be free of sharp edges, burrs, cracks, worn parts, or corrosion,





Any PVC-coated hardware must be free of cuts, rips, tears, holes, etc. in the coating to ensure non-conductivity. Also ensure that buckles and adjusters work smoothly.

WEBBING & STITCHING

Material must be free of frayed, cut, or broken fibers. Check for tears, abrasions, mold, burns, or discoloration. Inspect stitching; check for pulled or cut stitches. Broken stitches may be an indication that the harness has been impact loaded.



Contact with
flames

Cu
ho

OTHER



manufacturer or their designate. before returning to service.

REFERENCE STANDARDS:

OSHA 1910 - Subpart D – Walking-Working Surfaces; OSHA 1926 - Subpart M – Fall Protection; ANSI Z359 - Fall Protection & Arrest

SCAN THE CODE TO LEARN MORE ABOUT FALL PROTECTION



TO SCHEDULE FALL PROTECTION INSPECTIONS OR TRAINING, CALL 800-362-4601 OR VISIT MAZZELLACOMPANIES.COM